



**法兰闸阀**

Flange gate valves  
产品型号: Z41H  
Product Model  
公称口径: 15-800mm  
Nominal Diameter  
公称压力: 10.0-25.0MPa  
Nominal Pressure  
适用介质: 液体、气体 (Liquid, gas)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**大口径闸阀**

Large diameter gate valves  
产品型号: Z541H/Y  
Product Model  
公称口径: 15-1000mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、酸性介质等 (Water, oil, steam, acid medium etc)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**电动不锈钢闸阀**

Electric stainless steel gate valves  
产品型号: Z941H  
Product Model  
公称口径: 15-800mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、及酸、碱、氨、尿素、含硫天然气等 (Water, oil, steam, acid, alkali, Ammonia, urea, sulfur natural gas)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**伞齿轮闸阀**

Bevel gear gate valves  
产品型号: Z541H  
Product Model  
公称口径: 15-1000mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、酸性介质等 (Water, oil, steam, acid medium etc)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**气动闸阀**

Pneumatic gate valves  
产品型号: Z6S41H  
Product Model  
公称口径: 50-600mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽 (Water, oil, steam)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**电动法兰闸阀**

Electric flange gate valves  
产品型号: Z941H  
Product Model  
公称口径: 15-1000mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、酸性介质等 (Water, oil, steam, acid medium etc)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**不锈钢闸阀**

Stainless steel gate valves  
产品型号: Z41W  
Product Model  
公称口径: 15-800mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、及酸、碱、氨、尿素、含硫天然气等 (Water, oil, steam, acid, alkali, Ammonia, urea, sulfur natural gas)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**自密封闸阀**

Since the hermetic seal gate valves  
产品型号: YZ540H/Y  
Product Model  
公称口径: 6"-16"mm  
Nominal Diameter  
公称压力: 2500LB  
Nominal Pressure  
适用介质: 水、油品、蒸汽、酸、碱 (Water, oil, steam, acid, alkali)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**不锈钢低温闸阀**

Low temperature stainless steel gate valves  
产品型号: DZ41Y  
Product Model  
公称口径: 15-1200mm  
Nominal Diameter  
公称压力: 1.0-6.4MPa  
Nominal Pressure  
适用介质: 天然气、液氨 (Natural gas, liquid ammonia)  
Suitable Medium  
适用温度: -196°C-300°C  
Suitable temperature



**吹2高温闸阀**

Blow 2 high temperature valve  
产品型号: ZZ40H/Y  
Product Model  
公称口径: 50-400mm  
Nominal Diameter  
公称压力: 1.6-4.0MPa  
Nominal Pressure  
适用介质: 烟气、粉末状、颗粒状 (Flue gas, powder, granule)  
Suitable Medium  
适用温度: -29°C-550°C  
Suitable temperature



**美标法兰闸阀**

American standard flange gate valves  
产品型号: Z40H  
Product Model  
公称口径: 15-800mm  
Nominal Diameter  
公称压力: 150-900LB  
Nominal Pressure  
适用介质: 液体、气体 (Liquid, gas)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**苏式闸阀**

Sushi gate valves  
产品型号: Z41W  
Product Model  
公称口径: 10-1000mm  
Nominal Diameter  
公称压力: 1.6-16.0MPa  
Nominal Pressure  
适用介质: 水、石油、天然气等 (Water, oil, natural gas, etc)  
Suitable Medium  
适用温度: -29°C-600°C  
Suitable temperature



**真空隔离阀**

Vacuum isolation valves  
产品型号: NKZ41H、NKZ44H、NKZ944H、NKZ941H  
Product Model  
公称口径: 15-1200mm  
Nominal Diameter  
公称压力: 1.0-10.0MPa  
Nominal Pressure  
适用介质: 水、蒸汽等 (Water, steam, etc)  
Suitable Medium  
适用温度: -29°C-550°C  
Suitable temperature



**铬钼钢闸阀**

Chromium MuGang gate valves  
产品型号: Z41Y-4G  
Product Model  
公称口径: 80-800mm  
Nominal Diameter  
公称压力: 1.6-16.0MPa  
Nominal Pressure  
适用介质: 水、油品、蒸汽、等 (Water, oil, steam, etc)  
Suitable Medium  
适用温度: -29°C-540°C  
Suitable temperature



**波纹管闸阀**

Bellows gate valves  
产品型号: WZ41H/Y  
Product Model  
公称口径: 15-450mm  
Nominal Diameter  
公称压力: 1.0-1.6MPa  
Nominal Pressure  
适用介质: 水、蒸汽、油品 (Water, steam, oil)  
Suitable Medium  
适用温度: -29°C-425°C  
Suitable temperature



**保温闸阀**

Insulation gate valves  
产品型号: BZ41W、BZ41Y  
Product Model  
公称口径: 15-300mm  
Nominal Diameter  
公称压力: 1.6-6.4MPa  
Nominal Pressure  
适用介质: 酸类、碱类 (Acid, alkali class)  
Suitable Medium  
适用温度: -29°C-425°C  
Suitable temperature